



**SPECIFICATIONS**

Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Withstanding Voltage: 1500V AC/minute  
 Material: Nylon 66,UL94V-2  
 Color: Black  
 Q'ty: 1000/Bag

Circuits	Dimensions	
	A	B
2	2.50	8.00
3	5.00	10.50
4	7.50	13.00
5	10.00	15.50
6	12.50	18.00
7	15.00	20.50
8	17.50	23.00
9	20.00	25.50
10	22.50	28.00
11	25.00	30.50
12	27.50	33.00

**REVISION RECORD**

REV.	DATE	DESCRIPTION	CHANGE	APPROVE

**TOLERANCE**

.0±0.25
0.00±0.20
0.000±0.15

**DRAW**

DESIGN	
CHECK	
APPROVE	
VERSION	TH1

**SCALE**

1:1	
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	



PART NO.	C2521H02-NP
DESCRITON	2.50mm PITCH HOUSING-PLUG
DRAWING NO.	

TEL:0769-87299998 FAX:0769-87299968 E-Mail:uniconn@163.com WEB:http://www.uniconn.cn